## § 63.460

## Subpart T—National Emission Standards for Halogenated Solvent Cleaning

SOURCE: 59 FR 61805, Dec. 2, 1994, unless otherwise noted.

## §63.460 Applicability and designation of source.

(a) The provisions of this subpart apply to each individual batch vapor, in-line vapor, in-line cold, and batch cold solvent cleaning machine that uses any solvent containing methylene chloride (CAS No. 75-09-2),perchloroethylene (CAS No. 127-18-4), trichloroethylene (CAS No. 79-01-6), 1,1,1-trichloroethane (CAS No. 71-55-6), carbon tetrachloride (CAS No. 56-23-5) or chloroform (CAS No. 67-66-3), or any combination of these halogenated HAP solvents, in a total concentration greater than 5 percent by weight, as a cleaning and/or drying agent. The concentration of these solvents may be determined using EPA test method 18, material safety data sheets, or engineering calculations. Wipe cleaning activities, such as using a rag containing halogenated solvent or a spray cleaner containing halogenated solvent are not covered under the provisions of this subpart.

(b) Except as noted in appendix C (General Provisions Applicability to Subpart T) of this subpart, the provisions of subpart A of this part (General Provisions) apply to owners or operators of any solvent cleaning machine meeting the applicability criteria of paragraph (a) of this section.

(c) Each solvent cleaning machine subject to this subpart that commences construction or reconstruction after November 29, 1993, shall achieve compliance with the provisions of this subpart immediately upon startup or by December 2, 1994, whichever is later.

(d) Each solvent cleaning machine subject to this subpart that commenced construction or reconstruction on or before November 29, 1993, shall achieve compliance with the provisions of this subpart no later than December 2, 1997. Except that, any machine that commences construction or reconstruction on or before November 29, 1993, that does not use halogenated hazardous air pollutant (HAP) solvent on De-

cember 2, 1994, shall, if the machine begins use of halogenated HAP solvent after December 2, 1994, achieve compliance with the provisions of this subpart no later than December 2, 1997, or 60 days after commencing use of halogenated HAP solvent covered under this subpart whichever is later.

(e) In delegating implementation and enforcement authority to a State under section 112(d) of the Act, the authority contained in paragraph (f) of this section shall be retained by the Administrator and not transferred to a State.

(f) The authority conferred in  $\S63.463(d)(9)$  and  $\S63.469$  will not be delegated to any State.

[59 FR 61805, Dec. 2, 1994; 59 FR 67750, Dec. 30, 1994; 60 FR 29485, June 5, 1995]

## §63.461 Definitions.

Unless defined below, all terms used in this subpart are used as defined in the 1990 Clean Air Act, or in subpart A of 40 CFR part 63:

Administrator means the Administrator of the United States Environmental Protection Agency or his or her authorized representative (e.g., State that has been delegated the authority to implement the provisions of this part.)

Air blanket means the layer of air inside the solvent cleaning machine freeboard located above the solvent/air interface. The centerline of the air blanket is equidistant between the sides of the machine.

Automated parts handling system means a mechanical device that carries all parts and parts baskets at a controlled speed from the initial loading of soiled or wet parts through the removal of the cleaned or dried parts. Automated parts handling systems include, but are not limited to, hoists and conveyors.

Batch cleaning machine means a solvent cleaning machine in which individual parts or a set of parts move through the entire cleaning cycle before new parts are introduced into the solvent cleaning machine. An open-top vapor cleaning machine is a type of batch cleaning machine. A solvent cleaning machine, such as a ferris wheel or a cross-rod degreaser, that